

WHAT IS CLAIMED IS:

1. A network device connected to a network and having a plurality of controllers, comprising:

5 a plurality of databases disposed in distributed fashion on respective ones of the plurality of controllers and storing management information relating to respective ones of the controllers; and

10 a plurality of agents distributed on the plurality of controllers;

wherein each of the plurality of agents has means for communicating with one another, means for executing distributed processing of messages issued from a network manager, and means for generating responses to these
15 messages.

2. The network device according to claim 1, wherein at least one agent among the plurality thereof functions as a master agent and the other agents function as subagents; and

20 each of said agents communicates with one another using a network manager that manages the network, and a protocol for management information exchange between the network manager and said network device.

3. The network device according to claim 2, wherein
25 said master agent includes:

means for separating a message issued from a network manager into a first message containing

management information to be processed by the master agent and a second message containing management information other than said management information to be processed;

- 5 response generating means for generating response information with regard to the first message; and
 means for notifying subagents of the second message.

4. The network device according to claim 3, wherein
10 said master agent includes:

 means for receiving response messages sent back from said subagents;

- reconstruction means for reconstructing a response message, which is to be sent back to the network
15 manager, from the response messages and the response information that has been generated by said response generating means; and

- means for sending the response message, which has been reconstructed by said reconstruction means, back to
20 said network manager.

5. The network device according to claim 2, wherein each subagent includes:

- means for separating a second message, which has been received from said master agent, into a third
25 message containing management information to be processed by the subagent and a fourth message

- containing management information other than said management information to be processed;

response generating means for generating response information with regard to the third message; and

5 means for notifying other subagents of the fourth message.

6. A method of controlling a network device connected to a network and having a plurality of controllers, comprising the steps of:

10 disposing a plurality of databases in distributed fashion on respective ones of the plurality of controllers, said databases storing management information relating to respective ones of the controllers; and

15 allowing a plurality of agents distributed on the plurality of controllers to communicate with one another, thereby executing distributed processing of messages issued from a network manager and generating responses to these messages.

20 7. The method according to claim 6, wherein at least one agent among the plurality thereof functions as a master agent and the other agents function as subagents; and

each of said agents communicates with one another
25 using a network manager that manages the network, and a protocol for management information exchange between the network manager and said network device.

8. The network device according to claim 7, wherein said master agent:

separates a message issued from a network manager into a first message containing management information to be processed by the master agent, and a second message containing management information other than said management information to be processed;

generates response information with regard to the first message; and

10 notifies subagents of the second message.

9. The method according to claim 8, wherein said master agent:

receives response messages sent back from said subagents;

15 reconstructs a response message, which is to be sent back to the network manager, from the response messages and the response information that has been generated; and

sends the reconstructed response message to said network manager.

10. The method according to claim 8, wherein each subagent:

separates a second message, which has been received from said master agent, into a third message containing management information to be processed by the subagent and a fourth message containing management information other than said management information to be processed;

generates response information with regard to the third message; and

notifies other subagents of the fourth message.

11. A computer program for implementing, by computer, a
5 master agent which includes:

means for separating a message issued from a network manager into a first message containing management information to be processed, and a second message containing management information other than
10 said management information to be processed;

response generating means for generating response information with regard to the first message; and

means for notifying a peripheral device of the second message.

15 12. The computer program according to claim 11, wherein said master agent further includes:

means for receiving a response message sent back from said peripheral device;

reconstruction means for reconstructing a response
20 message, which is to be sent back to the network manager, from the response message and the response information that has been generated by said response generating means; and

means for sending the response message, which has
25 been reconstructed by said reconstruction means, back to said network manager.

13. A computer program for implementing, by computer:

means for separating a message received from a controller into a first message containing management information to be processed and a second message containing management information other than said management information to be processed;

response generating means for generating response information with regard to the first message; and

means for notifying other subagents of the second message.

- 10 14. A computer-readable storage medium storing a computer program for implementing, by computer, a master agent which includes:

means for separating a message issued from a network manager into a first message containing management information to be processed, and a second message containing management information other than said management information to be processed;

response generating means for generating response information with regard to the first message; and

- 20 means for notifying a peripheral device of the second message.

- 15 15. The computer-readable storage medium according to claim 14, wherein said master agent further includes:

25 means for receiving a response message sent back from said peripheral device;

reconstruction means for reconstructing a response message, which is to be sent back to the network

manager, from the response message and the response information that has been generated by said response generating means; and

means for sending the response message, which has
5 been reconstructed by said reconstruction means, back to said network manager.

16. A computer-readable storage medium storing a computer program for implementing, by computer:

means for separating a message received from a
10 controller into a first message containing management information to be processed and a second message containing management information other than said management information to be processed;

response generating means for generating response
15 information with regard to the first message; and

means for notifying other subagents of the second message.

17. A network controller connected to a peripheral device and to a communication line, comprising:

20 receiving means for receiving data from a management apparatus via the communication line;

discriminating means for discriminating the data, which has been received by said receiving means, as data to be processed by the network controller and data to be
25 processed by the peripheral device; and

processing means for sending the peripheral device, and causing the peripheral device to process, data that

said discriminating means has discriminated as being data to be processed by the peripheral device, and for processing data that said discriminating means has discriminated as being data to be processed by the
5 network controller.

18. The network controller according to claim 17, further comprising holding means for holding information relating to the network controller, wherein said processing means processes the data using the
10 information held by said holding means.

19. The network controller according to claim 17, further comprising connecting means capable of being connected to a plurality of peripheral devices, wherein said discriminating means discriminates, with regard to
15 each connected peripheral device, data to be transmitted to and processed by said peripheral device.

20. A peripheral device connected to a communication line via the network controlled set forth in claim 8, comprising:

20 receiving means for receiving data from a management apparatus via said network controller; and
processing means for processing data, which has been received by said receiving means, upon referring to a database holding information relating to said
25 peripheral device.

21. A method of controlling a network controller connected to a peripheral device and to a communication line, comprising:

5 a receiving step of receiving data from a management apparatus via the communication line;

a discriminating step of discriminating the data, which has been received at said receiving step, as data to be processed by the network controller and data to be processed by the peripheral device; and

10 a processing step of sending the peripheral device, and causing the peripheral device to process, data that said discriminating step has discriminated as being data to be processed by the peripheral device, and for processing data that said discriminating step has
15 discriminated as being data to be processed by the network controller.

22. The method according to claim 21, further comprising a holding step of holding information relating to the network controller, wherein said
20 processing step processes the data using the information held at said holding step.

23. The method according to claim 21, wherein said discriminating step discriminates, with regard to each connected peripheral device, data to be transmitted to
25 and processed by said peripheral device.

24. A computer program for implementing control in a network controller connected to a peripheral device and to a communication line, comprising:

a receiving step of receiving data from a management apparatus via the communication line;

a discriminating step of discriminating the data, which has been received at said receiving step, as data to be processed by the network controller and data to be processed by the peripheral device; and

a processing step of sending the peripheral device, and causing the peripheral device to process, data that said discriminating step has discriminated as being data to be processed by the peripheral device, and for processing data that said discriminating step has discriminated as being data to be processed by the network controller.

25. The computer program according to claim 24, further comprising a holding step of holding information relating to the network controller, wherein said processing step processes the data using the information held at said holding step.

26. The computer program according to claim 24, wherein said discriminating step discriminates, with regard to each connected peripheral device, data to be transmitted to and processed by said peripheral device.

27. A computer-readable storage medium storing a computer program for implementing control in a network

controller connected to a peripheral device and to a communication line, said program comprising:

a receiving step of receiving data from a management apparatus via the communication line;

5 a discriminating step of discriminating the data, which has been received at said receiving step, as data to be processed by the network controller and data to be processed by the peripheral device; and

10 a processing step of sending the peripheral device, and causing the peripheral device to process, data that said discriminating step has discriminated as being data to be processed by the peripheral device, and for processing data that said discriminating step has discriminated as being data to be processed by the network controller.

15 28. The storage medium according to claim 27, wherein said program further comprises a holding step of holding information relating to the network controller, wherein said processing step processes the data using the information held at said holding step.

20 29. The storage medium according to claim 27, wherein said discriminating step discriminates, with regard to each connected peripheral device, data to be transmitted to and processed by said peripheral device.

25 30. A network device connected to a communication line and including a network controller and a peripheral processing unit, said network controller having:

receiving means for receiving data from a
management apparatus via the communication line;

discriminating means for discriminating the data,
which has been received by said receiving means, as data
5 to be processed by the network controller and data to be
processed by the peripheral processing unit; and

first processing means for sending the peripheral
processing unit, and causing said peripheral processing
unit to process, data that said discriminating means has
10 discriminated as being data to be processed by the
peripheral processing unit, and for processing data that
said discriminating means has discriminated as being
data to be processed by the network controller; and

said peripheral processing unit has:

15 receiving means for receiving data that said
discriminating means has discriminated as being data to
be processed by said peripheral processing unit; and

second processing means for processing data, which
has been received by said receiving means, upon
20 referring to a database holding information relating to
the peripheral processing unit.

31. The network device according to claim 30, further
comprising holding means for holding information
relating to the network controller per se, wherein said
25 first processing means processes the data using the
information held by said holding means.

32. The network device according to claim 30, further comprising means capable of being connected to a plurality of peripheral processing units, wherein said discriminating means discriminates, with regard to each
5 connected peripheral processing unit, data to be transmitted to and processed by said peripheral processing unit.

33. A device controller externally connected at two ends, comprising:

10 a database;

means which, if a message received from upstream contains management information corresponding to an entry in said database, is for generating response information by processing the management information in
15 accordance with the message;

means which, if the message contains other management information, is for generating a second message containing this management information and transmitting the second message downstream; and

20 means for reconstructing a response message by combining the response information with the second message received from downstream, and transmitting the response message upstream.

34. A controller method for a device externally
25 connected at two ends, comprising the step of:

if a message received from upstream contains management information corresponding to an entry in a

database, generating response information by processing the management information in accordance with the message;

if the message contains other management
5 information, generating a second message containing this management information and transmitting the second message downstream;

reconstructing a response message by combining the response information with the second message received
10 from downstream; and

transmitting the response message upstream.

35. A computer program, which uses a database, for implementing by computer:

means which, if a message received from upstream
15 contains management information corresponding to an entry in said database, is for generating response information by processing the management information in accordance with the message;

means which, if the message contains other
20 management information, is for generating a second message containing this management information and transmitting the second message downstream; and

means for reconstructing a response message by combining the response information with the second
25 message received from downstream, and transmitting the response message upstream.